Sweeping Performance and Applications

- True Regenerative Air Performance
- **South Coast AQMD Rule 1186 PM**₁₀ Certified
- High Dump Flexibility
 - Isuzu Chassis Dump Height 72 inches
 - Freightliner Chassis Dump Height 82.5 inches
- Municipal, Construction and Industrial Sweeping
- Crowned, Cracked and Irregular Paved Street and Roads
- BMP (Best Management Practice) for Stormwater Quality
- Porous and Permeable Pavements
- Airport Runways and Taxiways
- BMP for Fugitive Dust Control
- Industrial Facility Cleaning
- Asphalt and Concrete



Dumping into a Low-Profile 30 yard Container



Dumping into a 30 yard Container





Sweeping Business Districts



Sweeping Residential Areas







Attendees review components of the pick-up Instructor reviews proper maintenance, removal head assembly during removal and installation. and installation of the blower assembly.

Highlights of the TYMCO Service School

- The Regenerative Air System
- Servicing the Blower, Dust Separator and Pick-up Head
- Hydraulic, Electrical and Water System Review
- Rebuild and Repair Small Parts and Components
- Using the BlueLogic[®] Control System
- Manufacturing Facility Tour This product is protected by numerous U.S. and Inter







MODEL 600° COMDEX°



MODEL 600° CNG





TYMCO REGENERATIVE AIR SWEEPERS are South Coast AQMD Rule 1186 PM₁₀ Certified 1218 - 7M - 01SM © TYMCO Inc. 2018

TYMCO, Inc. • P.O. Box 2368 • Waco, TX 76703-2368 • (254) 799-5546 • FAX (254) 799-2722









Please Recycle

REGENERATIVE AIR SWEEPERS



1-800-258-9626

www.tymco.com

MADE IN WACO, TEXAS USA





From The People Who Invented Regenerative Air Sweeping!

Up to 150 gallons of water for dust control around the gutter brooms and inside the hopper.

BlueLogic[®] **Control System**

The BlueLogic[®] *Control System is* the TYMCO multiplex electronics platform that delivers reduced wiring and advanced diagnostics.



In-cab controls are center mounted and illuminated for ease of operation from either driving position. Switches integrate multicolor LEDs giving operators instant feedback on sweeper functions.



The color touchscreen display delivers on-board diagnostics for the TYMCO BlueLogic[®] Control System and the auxiliary engine's ECU (Engine Control Unit). Service reminders are displayed for the auxiliary engine and hydraulic system fluids and filters.

The TYMCO patented 36 inch Gutter Broom is illuminated for night sweeping. Dual brooms are available as an option. Brooms are also available with optional Hydraulic Tilt Adjusters, Variable Speed Control and Drop Down Mode allowing the brooms to work in an outboard or inboard position.

Additional Sweeper Options

- Non-Magnetic, Low Carbon, High Chrome Stainless Steel Hopper and Components
- Hi/Low Pressure Washdown System
- Auxiliary Hand Hose



Sound Reduction Engineering[®] (SRE) allows the Model 435 to sweep in areas where low noise levels are desirable. SRE isolates various noise sources on the sweeper and addresses those areas through elimination or redesign. SRE reduces average sound power by over 3.5 dBA.

COMDE

The COMDEX[®] Package utilizes the short 132.5 inch wheelbase of the Isuzu NPR-XD chassis to provide storage, either a 72.5 or 145 gallon water capacity and signage space for the customer. Acrylic capped ABS plastic doors on each side of the sweeper provide a lockable, covered storage area in addition to the tool rack on the front of the COMDEX module.

Special options are available for your individual requirements. Contact your local dealer or TYMCO

Chassis Options and Features



Isuzu[®] NQR

Cabover Chassis

• 17,950 lb. GVW

- 150 Gallons of Water for Dust Control
- 150 in. Wheelbase
- 72 in. Dump Height
- Dual Steering Optional
- Remote Controlled Heated Power Mirrors Optional

Pick-Up Head Front Curtain Lifter

Camera/Monitor System

Hopper Drain System

Hopper Deluge System



• 16.000 lb. GVW

- Requires COMDEX Package 72.5 or 145 Gallons of Water for Dust Control
- 132.5 in. Wheelbase
- 72 in. Dump Height
- Dual Steering Optional
- Remote Controlled Heated Power Mirrors Optional

Isuzu[®] NPR-XD **Cabover Chassis**



- 25,500 lb. GVW 8000 lb. Payload
- 150 Gallons of Water for Dust Control
- 153 in. Wheelbase
- 82.5 in. Dump Height
- Dual Tilt Steering, and Dual Instrumentation
- Dual Adjustable High Back Air Suspension Seats
- Remote Controlled Heated Power Mirrors

Freightliner® M2-106 **Conventional Cab Chassis**