



600[®]
AIR SWEEPER

GENERAL SPECIFICATIONS



MODEL 600[®] REGENERATIVE[®] AIR STREET SWEEPER
DIESEL AUXILIARY ENGINE / DIESEL CABOVER CHASSIS

SWEEPER AUXILIARY ENGINE

Engine John Deere 4045 turbo FT4, 4 cyl.
Displacement.....275 in³ (4.5 L)
Power..... 99 HP @ 2200 RPM (74 kW)
Net torque.....315 lb-ft @ 1600 RPM (427 Nm)
Air cleaner Heavy duty, w/pre-cleaner, scavenge vacuum hose, and in-cab air restriction indicator w/gauge.
Remote oil filter..... Spin on, full flow
Auxiliary engine fuel tank shared with chassis
Diesel fuel tank capacity..... 51 gal (193 L)
DEF tank..... Dedicated
Capacity (volumetric) 5.4 gal (20.6 L)
Capacity (useable)..... 3.8 gal (14.4 L)
Auxiliary engine protection system
Fuel/water separator and separate fuel filter
Open crankcase ventilation (OCV) filter

BLOWER, Rubber Lined

Aluminum alloy, high volume, open face turbine
Purpose Creates blast and suction
Bearings(2) sealed lifetime lube, anti-friction
Bolt-on housing.....Steel w/abrasion resistant, replaceable liner
DriveHeavy duty power band

DUST SEPARATOR

TypeCyclonic, multipass, centrifugal separation
Size.....20 x 61 in cylindrical area (508 x 1549 mm)
Located adjacent to blower within hopper
Particulate removal achieved through 61 in (1549 mm) skimmer slot into skimmer hood
Hinged inspection door opened from hopper exterior
Abrasion resistant housing w/replaceable wear resistant liner

HOPPER

Capacity (volumetric)7.3 yd³ (5.6 m³)
Capacity (useable)6 yd³ (4.6 m³)
ConstructionWelded steel plate with integral stiffeners
Floor angle22°
Dump door opening.....84 x 44 in (2134 x 1118 mm)
Dumping methodHydraulic with raker bar
Dumping height 36 in (914 mm)

PICK-UP HEAD

TypeDual chamber
Function Delivers air blast and suction
Width (inside dimension) 87 in (2210 mm)
Std. Pick-up head area2610 in² (1.68 m²)
BAH[®] option area.....3567 in² (2.3 m²)
Suspension..... 4 springs, 2 drag links
Skids.....DUO SKID[®], long-life carbide
Suction hose diameter..... 14 in (356 mm)
Pressure hose diameter 14 in (356 mm)
Linear actuator - pressure bleeder w/gauge
Integral for leaf/light material pickup
Reverse pick-up head system

GUTTER BROOM, TWIN, Patented

Standard equipment includes floodlights and parabolic mirrors
DriveConstant speed non-reversible hydraulic motor
Adjustment.....Adjustable for down pressure, pattern and wear
Down pressureAutomatically adjusts to requirement
FlexibilityAll directions integral anti-damage "swing away" relief valve
Broom 43 in dia. (1092 mm) steel wire, vertical digger

HYDRAULIC SYSTEM

Operates gutter broom(s), dump and pick-up head
Drive Gear driven from auxiliary engine
Flow rate 8 GPM (30.3 LPM)
Reservoir ... 25 gal (94.6 L) w/80 mesh suction strainer, sight/temperature gauge, cooler
Filter..... 3 micron in-line
Temperature shutdown system

DUST CONTROL SYSTEM

Water spray nozzles for dust suppression
Pump Electric diaphragm
ReservoirsPolyethylene
330 gal (1249 L) total minimum
Filter 80 mesh in-line
Low water shut-offSafety shut-off with audible and visual indicator in cab
Spray nozzles:
Around pick-up head4
Gutter brooms (each)2
Hopper (inside)1
Hydrant fill hose w/storage area20 ft (6 m)

CONTROL SYSTEM

BlueLogic[®] Control System

Multiplexed electrical system includes hardware and TYMCO designed software that integrates the in-cab controls to the auxiliary engine and all sweeper functions; as well as provides intelligent safety features and on-board diagnostics (OBD) for the auxiliary engine and sweeper through the BlueLogic display.

BlueLogic Display

Pedestal mounted touchscreen display provides sweeper and auxiliary engine data to the operator and includes hour meters (trip and total) for the auxiliary engine, gutter brooms, pick-up head, blower, water pump, and BAH broom if applicable; sweeper odometer (records curb miles swept and sweeping hours), service reminders, custom reminders, overspeed warning, low water audible alarm, dust control system winterization guide, and OBD.

Interior Components

BlueLogic display, auxiliary fuse panel, illuminated control switches: pick-up head, gutter brooms, auxiliary engine RPM, leaf pressure bleeder, dust control water system nozzles, safety lights.

Exterior Components

Dump switch, BlueLogic multiplex module

SAFETY/WARNING DEVICES

Alternating LED rear flashers (2)
Back-up alarm
SAE Class 1/California Title 13 amber beacon light with limb guard - LED

OPTIONAL EQUIPMENT

AOD water pump w/washdown hose/spray gun
Abrasion protection package
Auto Sweep Interrupt (ASI)
Auxiliary hand hose 8 in dia. (203 mm)
Auxiliary hand hose hydraulic boom assist
Auxiliary hand hose catch basin cleaning package
Auxiliary hydraulic system
Broom Assist Pick-up Head (BAH[®])
Camera/monitor system
Extra water capacity 440 gal (1665 L) total (Peterbilt 220 only)
Gutter broom tilt adjuster(s) (left, right, or twin)
Gutter broom variable speed
Gutter broom drop-down
Hi/Low pressure washdown system
High output water system
Hopper deluge system
Hopper drain system
Lateral airflow nozzle
Liquid recovery system
Low emissions package (required for South Coast AQMD Rule 1186)
Magnet, light, standard, or heavy duty
Pick-up head curtain lifter
Pick-up head deluge
Shop air purge, dust control system
Spark resistant skids
Stainless steel options:
Hopper:
Hopper weldment
Dump door
Inspection doors
Raker plate
High capacity dust separator
Hopper screen
Blower housing
High capacity dust separator
Hopper drain
Paint color (other than TYMCO standard white)

Special options are available for your individual requirements. Contact your local dealer or TYMCO.

CABOVER CHASSIS AVAILABLE

Peterbilt 220
Autocar Xpert