







MODEL 600® REGENERATIVE® AIR STREET SWEEPER DIESEL AUXILIARY ENGINE / DIESEL CABOVER CHASSIS

SWEEPER AUXILIARY ENGINE
Engine John Deere 4045 turbo FT4, 4 cyl.
Displacement275 in ³ (4.5 L)
Power
Net torque315 lb-ft @ 1600 RPM (427 Nm)
Air cleaner Heavy
duty, w/pre-cleaner, scavenge vacuum hose,
and in-cab air restriction indicator w/gauge.
Remote oil filterSpin on, full flow
Auxiliary engine fuel tank shared with chassis
Diesel fuel tank capacity51 gal (193 L)
DEF tank
Capacity (volumetric) 5.4 gal (20.6 L)
Capacity (useable)3.8 gal (14.4 L)
Auxiliary engine protection system
Fuel/water separator and separate fuel filter Open crankcase ventilation (OCV) filter
Open crankcase ventilation (OCV) filter

BLOWER, Rubber Lined

Aluminum alloy, high volume, open face turbine Bearings(2) sealed lifetime lube, anti-friction Bolt-on housing......Steel w/abrasion resistant, replaceable liner DriveHeavy duty power band

DUST SEPARATOR, HIGH CAPACITY

TypeCyclonic, multipass, centrifugal separation Size20 x 61 in cylindrical area (508 x 1549 mm) Located adjacent to blower within hopper Particulate removal achieved through 61 in (1549 mm) skimmer slot into skimmer hood Hinged inspection door opened from hopper exterior

Abrasion resistant housing w/replaceable wear resistant liner

HOPPER

Capacity (volumetric)	7.3 yd³ (5.6 m³)
Capacity (useable)	6 yd³ (4.6 m³)
Construction	Welded steel plate
with integral stiffener	S
Floor angle	22°
Dump door opening	84 x 44 in
(2134 x 1118 mm)	
Dump method	Hydraulic with raker bar
Dump height	36 in (914 mm)

PICK-UP HEAD
Type Dual chamber
Width (inside dimension) 87 in (2210 mm)
Std. Pick-up head area2610 in ² (1.68 m ²)
BAH® option area3567 in ² (2.3 m ²)
Suspension 4 springs, 2 drag links
SkidsDUO SKID®, long-life carbide
Suction hose diameter14 in (356 mm)
Pressure hose diameter 14 in (356 mm)
Linear actuator - pressure bleeder w/gauge
Integral for leaf/light material pickup
Reverse pick-up head system

GUTTER BROOM, TWIN, Patented

Includes LED floodlights and parabolic mirrors
DriveConstant speed
non-reversible hydraulic motor
AdjustmentAdjustable for
down pressure, pattern and wear
Down pressure Automatic
FlexibilityAll directions integral
anti-damage "swing away" relief valve
Broom
steel wire, vertical digger

HYDRAULIC SYSTEM

Operates gutter broom(s), dump and pick-up Drive Gear driven from auxiliary engine Flow rate...... 8 GPM (30.3 LPM) Reservoir... 25 gal (94.6 L) w/80 mesh suction strainer, sight/temperature gauge, cooler Filter......3 micron in-line Temperature shutdown system

DUST CONTROL SYSTEM

Water spray nozzles for dust suppression

Pump	Electric diaphragm
Reservoirs	Polyethylene
330 gal (1249 L) total m	inimum
Filter	80 mesh in-line
Low water shut-off	Safety shut-off
with audible and visual i	ndicator in cab
Spray nozzles:	
Around pick-up head	4
Gutter brooms (each)	
Hopper (inside)	1
Hydrant fill hose w/storage	e area 20 ft (6 m)

CONTROL SYSTEM

BlueLogic® Control System

Multiplexed electrical system includes hardware and TYMCO designed software that integrates the in-cab controls to the auxiliary engine and all sweeper functions; as well as provides intelligent safety features and on-board diagnostics (OBD) for the auxiliary engine and sweeper through the BlueLogic display.

BlueLogic Display

Pedestal mounted touchscreen display provides sweeper and auxiliary engine data to the operator and includes hour meters (trip and total) for the auxiliary engine, gutter brooms, pick-up head, blower, water pump, and BAH broom if applicable; sweeper odometer (records curb miles swept and sweeping hours), service reminders, custom reminders, overspeed warning, low water audible alarm, dust control system winterization guide, and OBD.

Interior Components

BlueLogic display, auxiliary fuse panel,

illuminated control switches: pick-up head, gutter brooms, auxiliary engine RPM, leaf pressure bleeder, dust control water system nozzles, safety lights.

Exterior Components

Dump switch, BlueLogic Control Module (BCM)

SAFETY/WARNING DEVICES

Alternating LED rear flashers (2) Rear view camera system Back-up alarm

SAE Class 1/California Title 13 amber beacon light with limb guard - LED

OPTIONAL EQUIPMENT

AOD water pump w/washdown hose/spray gun Abrasion protection package Additional camera views - pick-up head, left gutter broom, right gutter broom Auto Sweep Interrupt (ASI)

Auxiliary hand hose 8 in dia. (203 mm) Auxiliary hand hose hydraulic boom assist Auxiliary hand hose catch basin cleaning package

Auxiliary hydraulic system

Broom Assist Pick-up Head (BAH®) Extra water capacity 440 gal (1665 L) total

(Peterbilt 220 onlý)

Gutter broom tilt adjuster(s) (left, right, or twin) Gutter broom variable speed

Gutter broom drop-down

Hi/Low pressure washdown system

High output water system Höpper deluge system

Hopper drain system Lateral airflow nozzle

Liquid recovery system

Low emissions package (required for South Coast AQMD Rule 1186)

Magnet, light, standard, or heavy duty

Pick-up head curtain lifter

Pick-up head deluge

Shop air purge, dust control system

Spark resistant skids

Stainless steel options: Hopper:

Höpper weldment Dump door

Inspection doors

Raker plate

High capacity dust separator

Hopper screen Blower housing

High capacity dust separator

Hopper drain

Paint color (other than TYMCO standard white)

Special options are available for your individual requirements. Contact your local dealer or TYMCO.

CABOVER CHASSIS AVAILABLE

Peterbilt 220

Autocar Xpert